



TYPE APPROVAL CERTIFICATE

Certificate no.:
TAA00002GJ
Revision No:
1

This is to certify:
that the Pressure Switch

with type designation(s)
B1T, B2T Series

issued to
Barksdale GmbH
Reichelsheim (Wetterau), Hessen, Germany

is found to comply with
DNV rules for classification – Ships, offshore units, and high speed and light craft

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Location classes:

Temperature	D
Humidity	B
Vibration	A
EMC	B
Enclosure	C (IP65)

Issued at **Hamburg** on **2024-10-02**

This Certificate is valid until **2029-10-15**.

DNV local unit: **Augsburg**

Approval Engineer: **Holger Jansen**



for **DNV**

Digitally signed by: Dariusz Lesniewski
Location: DNV Hamburg, Germany

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.



Form code: TA 251

Revision: 2023-09

www.dnv.com

Page 1 of 3

Product description

Bourdon Tube Pressure Switch B1T, B2T Series

Type	Range [bar]	Switching diff. [bar]	Test pressure [bar]
B1(2)T-x-12-GL	3,5 – 85	0.7 – 1.5	124
B1(2)T-x-12SS-GL	3.5 – 85	0.8 – 1.9	124
B1(2)T-x-32-GL	11 – 225	1.0 – 2.1	331
B1(2)T-x-32SS-GL	11 – 225	1.0 – 2.4	331
B1(2)T-x-48SS-GL	17 - 340	2.8 – 6.0	496

“x” – switch type: B, H, J, K, M, GB, GH, GM, AA, HH

Output: 1 c/o-contact (B1T..), 2 c/o-contacts (B2T..)

Contact rating: typical values (H, J, M) 125 – 250 Vac /10A
 6 – 24 Vdc / 0.5 A

Bourdon Tube:

Bronze = represents Phosphor Bronze Tube with SAE Brass Socket
 316 = represents Stainless Steel Tube Socket

Application/Limitation

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Type Approval documentation

Data sheets: B1T/B2T; 923-1496 Rev. J
 Drawings: 923-0309 Rev. G (pages 7 + 12)
 Operating characteristics HI-P Dia-Seal Piston Models
 Assembly Dwg. No. C98148
 Technical documentation 7.500 4.70
 Test reports: Environmental test report 081070 / 130171
 VDE Nr. 19375-9000-4001/A1A
 Type Approval Assessment Report issued at Augsburg on 2024-07-04

Tests carried out

Applicable tests according to DNV-CG-0339, August 2021.

Marking of product

The products to be marked with:

- Model name
- Manufacturer name
- Serial number

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE